

(12) **United States Patent**
Tu et al.

(10) **Patent No.:** **US 9,712,977 B2**
(45) **Date of Patent:** ***Jul. 18, 2017**

(54) **DETERMINING EXIT FROM A VEHICLE**

(56) **References Cited**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

U.S. PATENT DOCUMENTS

(72) Inventors: **Xiaoyuan Tu**, Sunnyvale, CA (US);
Anil K. Kandangath, San Francisco,
CA (US)

5,416,712 A	5/1995	Geier et al.
6,405,125 B1	6/2002	Ayed
6,407,698 B1	6/2002	Ayed
6,429,791 B2	8/2002	Quinn
6,909,964 B2	6/2005	Armstrong et al.
6,982,669 B2	1/2006	Coatantiec et al.
7,369,061 B1	5/2008	Sellers et al.
7,688,226 B2	3/2010	McCall
7,734,315 B2	6/2010	Rathus et al.

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

(21) Appl. No.: **15/043,243**

Kwapisz, Jennifer R., et al., "Activity Recognition Using Cell Phone Accelerometers," SensorKDD '10, Jul. 25, 2010, Washington, D.C., USA, 9 pages.

(22) Filed: **Feb. 12, 2016**

(Continued)

(65) **Prior Publication Data**

US 2016/0242008 A1 Aug. 18, 2016

Primary Examiner — Mong-Thuy Tran

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP

Related U.S. Application Data

(63) Continuation of application No. 14/065,224, filed on Oct. 28, 2013, now Pat. No. 9,264,862.

(60) Provisional application No. 61/866,490, filed on Aug. 15, 2013.

(51) **Int. Cl.**

H04W 24/00 (2009.01)

H04W 4/02 (2009.01)

H04W 4/04 (2009.01)

(52) **U.S. Cl.**

CPC **H04W 4/028** (2013.01); **H04W 4/046** (2013.01); **H04W 24/00** (2013.01)

(58) **Field of Classification Search**

CPC H04W 4/028; H04W 4/046; H04W 24/00

USPC 455/456.1; 701/2

See application file for complete search history.

(57)

ABSTRACT

Methods and mobile devices determine an exit from a vehicle. Sensors of a mobile device can be used to determine when the user is in a vehicle that is driving. The same or different sensors can be used to identify a disturbance (e.g., loss of communication connection from mobile device to a car computer). After the disturbance, an exit confidence score can be determined at various times, and compared to a threshold. A determination of the exit of the user can be determined based on the comparison of the exit confidence score to the threshold. The mobile device can perform one or more functions in response to the exit confidence score exceeding the threshold, such as changing a user interface e.g., of a navigation app) or obtaining a location to designate a parking location.

18 Claims, 9 Drawing Sheets

200

